## Intuitive Couplings with Advanced

# **NON-SPILL TECHNOLOGY**



Browse our online store, with more than 9,600 stock components and technologies, most ready to ship within 24 hours. 55GP Series couplings feature advanced non-spill technology to prevent leakage during disconnection, allowing for the highest level of performance. Optimal component designs produce reliable and cost-effective results, including improved product safety, reduced downtime, and a simplified process.

### **BUY ONLINE AT NORDSONMEDICAL.COM/SHOP**

Manufactured from a chemically-resistant, high-performance, glass-filled polypropylene, the material supports sterilization. The user-friendly interface provides for easy operation, and all 55GP couplings interconnect with other similar industry non-spill type couplings.

#### **FEATURES & BENEFITS**

- Advanced plastic thumb-latch couplings
- Non-spill technology to prevent leakage
- Chemically-resistant, glass-filled polypropylene
- Threaded and in-line straight (barbed) styles
- Couplings can interconnect with other industry non-spill couplings
- Operating pressure: Vacuum to 120 psi (8.3 bar)
- **Temperature:** 32° F to 160° F (0° C to 71° C)
- **Styles**: Threaded, In-line straight (barbed)

#### **MATERIALS**

- Bodies and terminations: Glass-filled polypropylene
- Internal valves: Glass-filled polypropylene
- Internal valve springs: 316 stainless steel
- Latch spring: Stainless steel
- **O-rings:** EPDM
- Thumb-latch: Glass-filled polypropylene

